

KSG52B

Hood, Integrated hood, Universale, Stainless steel, 52 cm, B



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 52 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709226176

AESTHETICS

Colour: Stainless steel • Finishing: Glass • Aesthetics: Universale • Design: Fully integrated • Material: Stainless Steel + Glass • Type of steel: Brushed • Glass Type: White

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led color: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 750 m³/h • Motor power: 235 W • No. of filters: 1 • Anti-grease filters: stainless steel 7 layer • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): C • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 68 kWh/a • Fluid Dynamic Efficiency (FDE): 22.6 • Lighting Efficiency (LE): 68 lux/W • Grease Filtering Efficiency (GFE): 65.9 % • Air flow at minimum speed (Q_{min}): 247 m³/h • Air flow at maximum speed (Q_{max}): 450 m³/h • Air flow at boost speed (Q_{boost}): 592 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 47 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 60 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 67 dB(A) • Power consumption in stand-by mode (P_s): 0.49 W • Time increase factor (F): 1.00 • Energy Efficiency Index: 62.7 • Measured air flow rate at best efficiency point (Q_{bep}): 327 m³/h • Measured air pressure at best efficiency point (P_{bep}): 404 Pa • Measured electric power input at best efficiency point (W_{bep}): 153 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 118 lux • Sound power level at highest setting (L_{wa}): 60 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 238 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 260 m³/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 140 W

SPEED 2

Extraction rate IEC 61591: 350 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 166 W

SPEED 3

Extraction rate IEC 61591: 460 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 184 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 630 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 207 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 275x534x272 • Width: 534 mm • Depth (mm): 272 mm • Product Height (mm): 275 mm • Net weight (kg): 10.000 kg

